

The Crown of Power Solution

General Features


System Specifications

This series is a complete solution for the lithium iron phosphate battery system for the home energy storage field. There are three types of wall-mounted, vertical structures and rack. The system is safe and reliable. It can be used in home storage, industrial and commercial energy storage and other fields.

System Specifications	
Voltage(V)	43.2~58.4V
Cell	3.2V100Ah
Module	16S1P
Number of parallel machines	15PCS
Nominal voltage(V)	51.2
Nominal Capacity(Ah)	100
Nominal Energy(kWh)	5.12
Maximum power output(kW)	5.12
Maximum discharge current(A)	100
Max <mark>imum cha</mark> rging current(A)	100
Cut- <mark>off voltag</mark> e(V)	40
Max <mark>imum cha</mark> rge voltage(V)	58.4
Cycles(25°C,0.5C,80%DOD)	≥6000
Charging temperature(°C)	0~55
Discharge temperature(°C)	-20~55
Operating humidity	<95%R.H
Com <mark>municatio</mark> n mode	CAN/RS485
Dry contact Customized	d by demand
Opti <mark>onal mod</mark> ules Bluetooth	n, 4G module
Product size(W*D*H,mm)	430*442*177
Packing size(W*D*H,mm)	535*527*290
Protection class	IP21
System weight(kg)	Approx 48
Certification IEC62619/UN38.3/MSDS	

Characteristic

- Safe, reliable and long life
- Dynamic identification, automatic paralleling, no need for DIP switches
- Support Bluetooth, mobile APP switching PCS protoco
- CAN/RS485/LAN interface
- Visualization, LCD screen display
- Flexible expansion, the number of parallel machines supports up to 15
- Supports mixed parallel of old and new batteries
- Remote intelligent upgrade maintenance



Panel silkscreen preview



Battery communication interface preview



Product renderings



Cell characteristic curve

